

## DATA SHEET

<b>Product Code</b>	AKQUICK T100
<b>Description</b>	DIMETHYLANILINE 99,9%
<b>Specifications;</b>	
Appearance	: Yellowish, Transparent, Foggy
Freezing Point	: $\geq 2,00$ °C
N-Metil Aniline Content	: $\leq 0,5\%$
Aniline Content	: $\leq 0,03\%$
Water Content	: $\leq 0,1\%$
N,N Dimethyl Aniline Content	: ( DMA ) $\geq 99,0\%$
CAS Nr	: 121-69-7
UN Nr	: 2253
<b>Applications</b>	AKQUICK T100 is used as accelerator with SMC, BMC and DMC type resins at room temperature or elevated temperatures.
<b>Usage &amp; Amount</b>	It is recommended to use 1% - 2% in general
<b>Packaging</b>	25kg PE Pail
<b>Handling &amp; Storage</b>	Must be kept between +5 C and +30 C. Keep pails tightly closed. Store and handle in a dry, well-ventilated place, away from sources of heat, ignition and direct sunlight in original packaging. Provide grounding and venting in order to prevent static electricity build-up. Avoid any contact with Organic Peroxides.
<b>Shelf Life</b>	1 Year For unopened packages at recommended storage conditions

